

Naaldhulslager BTM3021A-JTEKT - BTM3021A-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm3021a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾		
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type		
								With open ends	With closed end
30	38	21	—	23.4	40.4	12 000	BTM3021A		

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	29.987	30.000	37.967	37.992	45	—

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952471921
Binnendiameter	30 mm
Binnendiameter	1.181" inch
Buitendiameter	38 mm
Buitendiameter	1.496" inch
Dikte	21 mm
Dikte	0.827" inch
Gewicht	45 g
Verpakking	-
Standaard	Geen standaard

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE