

## Naaldhulslager BHTM3025-1-JTEKT - BHTM3025-1-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bhtm3025-1-jtekt>

Drawn cup needle roller bearings **Koyo**



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	Oil lub.	Caged type With open ends    With closed end
30	40	25	—	29.4	46.5	12 000 <b>BHTM3025-1</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	29.987	30.000	39.967	39.992	69	—

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250003226
Binnendiameter	30 mm
Buitendiameter	40 mm
Dikte	25 mm
Gewicht	69 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE