


Naaldhulslager BHTM3220A-JTEKT - BHTM3220A-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bhtm3220a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type With open ends With closed end
32	42	20	17.3	23.4	34.8	11 000	BHTM3220A

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	31.984	32.000	41.989 ⁽⁴⁾	42.014 ⁽⁴⁾	57	64

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250003233
Binnendiameter	32 mm
Buitendiameter	42 mm
Dikte	20 mm
Gewicht	57 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE