

# Naaldhulslager BKM354220-1UU-JTEKT - BKM354220-1UU-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bkm354220-1uu-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
35	42	20	—	13.3	22.8	5 700 <sup>1)</sup>	<b>BKM354220-1UU</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	34.984	35.000	41.967	41.992	38	—

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472195
Binnendiameter	35 mm
Buitendiameter	42 mm
Dikte	20 mm
Gewicht	38 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE