

## Naaldhulslager BTM3520-JTEKT - BTM3520-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm3520-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Caged type With open ends    With closed end
35	42	20	17.3	23.4	47.0	11 000	<b>BTM3520</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	34.984	35.000	41.989 <sup>(4)</sup>	42.014 <sup>(4)</sup>	43	49

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472225
Binnendiameter	35 mm
Buitendiameter	42 mm
Dikte	20 mm
Gewicht	43 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE