

## Naaldhulslager BTM3520-JTEKT - BTM3520-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm3520-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
35	42	20	17.3	23.4	47.0	11 000	<b>BTM3520</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φF)	Housing bore dia. (φT)	min.	max.	With open ends	With closed end
—	—	34.984	35.000	41.989 <sup>(4)</sup>	42.014 <sup>(4)</sup>	43	49

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472225
Binnendiameter	35 mm
Buitendiameter	42 mm
Dikte	20 mm
Gewicht	43 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE