

## Naaldhulslager BTM3820A-JTEKT - BTM3820A-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm3820a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
F <sub>w</sub>	D	C	b min.	C <sub>10</sub>	C <sub>90</sub>	Oil lub.	Caged type With open ends    With closed end
38	48	20	17.3	27.1	44.5	9 500	<b>BTM3820A</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	37.984	38.000	47.967	47.992	67	76

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3616060465412
Binnendiameter	38 mm
Buitendiameter	48 mm
Dikte	20 mm
Gewicht	67 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE