

Naaldhulslager 40BTM4716-JTEKT - 40BTM4716-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/40btm4716-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|---|
| F_w | D | C | b min. | C_r | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 40 | 47 | 16 | 13.3 | 18.7 | 37.1 | 9 400 | 40BTM4716 |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (F6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 39.984 | 40.000 | 46.967 | 46.992 | 39 | 44 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952472522 |
| Binnendiameter | 40 mm |
| Buitendiameter | 47 mm |
| Dikte | 16 mm |
| Gewicht | 39 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE