


## Naaldhulslager 40MKM4716-JTEKT - 40MKM4716-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/40mkm4716-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
40	47	16	13.3	18.7	37.1	9 400	40MKM4716

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6)		Housing bore dia. (N7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	39.984	40.000	46.967	46.992	39	44

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472539
Binnendiameter	40 mm
Buitendiameter	47 mm
Dikte	16 mm
Gewicht	44 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE