

## Naaldhulslager BTM4015-JTEKT - BTM4015-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm4015-jtekt>

Drawn cup needle roller bearings **Koyo**



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	
40	50	15	—	20.2	31.2	9 100	BTM4015

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	39.984	40.000	49.967	49.992	54	—

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472591
Binnendiameter	40 mm
Buitendiameter	50 mm
Dikte	15 mm
Gewicht	54 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE