

Naaldhulslager BTM505816J-JTEKT - BTM505816J-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm505816j-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|---------------------------|
| F _w | D | C | b min. | C _r | C _{0r} | Oil lub. |
| 50 | 58 | 16 | — | 21.9 | 43.8 | 7 500 |
| | | | | | | BTM505816J |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 49.984 | 50.000 | 57.961 | 57.991 | 54 | — |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952472867 |
| Binnendiameter | 50 mm |
| Buitendiameter | 58 mm |
| Dikte | 16 mm |
| Gewicht | 54 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE