


## Naaldhulslager BTM5030-JTEKT - BTM5030-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm5030-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
50	62	30	27.3	52.8	98.5	7 300	<b>BTM5030</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6)		Housing bore dia. (H7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	49.984	50.000	61.961	61.991	153	173

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952472973
Binnendiameter	50 mm
Buitendiameter	62 mm
Dikte	30 mm
Gewicht	153 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE