

Naaldhulslager BTM727915AJ-JTEKT - BTM727915AJ-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm727915aj-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-------|-----|-------------------------|-------|--------------------------------------|----------|---------------------------|-----------------|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type | |
| | | | | | | | With open ends | With closed end |
| 71.60 | 78.60 | 15 | — | 22.9 | 61.9 | 5 400 | BTM727915AJ | |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 71.581 | 71.600 | 78.561 | 78.591 | 66 | — |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952473031 |
| Binnendiameter | 71.6 mm |
| Buitendiameter | 78.6 mm |
| Dikte | 15 mm |
| Gewicht | 66 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE