

## Rollager NN3030-JTEKT - NN3030-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/roll/nn3030-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.	
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>C</i>	<i>C<sub>07</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
150	225	56	2.1	—	208	334	587	2 500	3 000	NN3030

  

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d<sub>s</sub></i>		<i>D<sub>s</sub></i>		<i>r<sub>s</sub></i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		161	—	—	214	208	2	7.74	7.50

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250033377
Binnendiameter	150 mm
Buitendiameter	225 mm
Dikte	56 mm
Gewicht	7740 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE