

Naaldhulslager

20NQ2717-JTEKT - 20NQ2717-JTEKT

https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/20nq2717-jtekt

Machined ring needle roller bearings Koyo

$F_{W\text{ 29 ~ 37 mm}}$

Without inner ring

NQ, NQS

Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.		Without inner ring
20	—	27	17	0.3	14.7	20.4	22 000	20NQ2717

Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.
With inner ring	d_a	D_a	r_a	Without inner ring	With inner ring
	min.	max.	max.	—	—
—	—	25	0.3	0.024	—

[Note]

1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.

[Remark]

Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477398
Binnendiameter	20 mm
Buitendiameter	27 mm
Dikte	17 mm
Gewicht	24 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE