

Naaldhulslager NQ20-16D-JTEKT - NQ20-16D-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nq20-16d-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.		Without inner ring	
20	—	28	16	—	12.0	18.2	23 000	NQ20/16D	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d ₁	D ₁	r ₁	0.030	—				
	max.	max.	max.						
	—	26	0.3						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250033674
Binnendiameter	20 mm
Buitendiameter	28 mm
Dikte	16 mm
Gewicht	30 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE