

Naaldhulslager 20NQ3315D-JTEKT - 20NQ3315D-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/20nq3315d-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
20	—	33	15	14.0	16.9	21 000	20NQ3315D	
		Mounting dimensions (mm)			Weight Mass (kg)		Applicable inner ring No.	
		d_a	D_a	r_a	Without inner ring	With inner ring		
		min.	max.	max.	—	—	—	
		—	29	0.6	0.052	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477473
Binnendiameter	20 mm
Buitendiameter	33 mm
Dikte	15 mm
Gewicht	52 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE