

## Naaldhulslager NQ12-10-JTEKT - NQ12-10-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nq12-10-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
 $F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$C_r$	$C_{10}$	Oil lub.		Without inner ring	
12	—	19	10	—	5.9	6.3	35 000	<b>NQ12/10</b>	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
		$d_a$	$D_a$	$r_a$	Without inner ring	With inner ring			
		max.	max.	max.	—	—			
		—	17	0.3	0.010	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477541
Binnendiameter	12 mm
Buitendiameter	19 mm
Dikte	10 mm
Gewicht	10 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE