

# Naaldhulslager NQS15-16-JTEKT - NQS15-16-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nqs15-16-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>e</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.		Without inner ring	
15	—	26	16	—	13.4	14.8	28 000	<b>NQS15/16</b>	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				d <sub>1</sub> min.	D <sub>1</sub> max.	r <sub>1</sub> max.	Without inner ring	With inner ring	
				—	24	0.3	0.034	—	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477619
Binnendiameter	15 mm
Buitendiameter	26 mm
Dikte	16 mm
Gewicht	34 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE