


Naaldhulslager NA4900-JTEKT - NA4900-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/na4900-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_w 29 – 37 mm
With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring
F _w	d	D	B	B _i	C _r	C _{10r}	Oil lub.			
14	10	22	13	—	0.3	7.6	9.1	31 000	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					d _i min.	D _o max.	r _a max.	Without inner ring	With inner ring	
NA4900					12	20	0.3	0.017	0.025	IRM101413

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952477787
Binnendiameter	10 mm
Buitendiameter	22 mm
Dikte	13 mm
Gewicht	25 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE