


Rollager NA4905UU-JTEKT - NA4905UU-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/roll/na4905uu-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 – 37 mm

With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring |
|--------------------------|----|----|----|-------------------------|-----------------|------------------------------------|--|---|-----------------------------------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | | | |
| 30 | 25 | 42 | 17 | 18.4 | 22.4 | 6 800 | | — | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| NA4905UU | | | | — | 0.092 | IRM253018 | | | |

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952482668 |
| Binnendiameter | 25 mm |
| Buitendiameter | 42 mm |
| Dikte | 17 mm |
| Gewicht | 92 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE