


Rollager 25NQI4425A-JTEKT - 25NQI4425A-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/roll/25nqi4425a-jtekt>

Machined ring needle roller bearings **Koyo**
F_W 29 ~ 37 mm
With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F _w	d	D	B	B ₁	C _r	C _{0r}	Oil lub.		Without inner ring	
30	25	44	25	25.5	36.0	48.8	14 000		—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
					d ₁	D ₁	r ₁			
					min.	max.	max.			
					25NQI4425A	27	42	0.3		
								0.161		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952482767
Binnendiameter	25 mm
Buitendiameter	44 mm
Dikte	25 mm
Gewicht	161 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE