


Rollager NA49-28R-JTEKT - NA49-28R-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/roll/na49-28r-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

With inner ring



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring | |
|--------------------------|-----|-----|-----|-------|-------------------------|-----------------|--|-------|-----------------------------------|-----------|
| F_w | d | D | B | B_1 | C_r | C_{10} | Oil lub. | | | |
| 32 | 28 | 45 | 17 | | 25.0 | 33.8 | 14 000 | | — | |
| Mounting dimensions (mm) | | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | | Without inner ring | With inner ring | | | | |
| NA49/28R | | | | | 30 | 43 | 0.3 | 0.075 | 0.099 | IRM283217 |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952482828 |
| Binnendiameter | 28 mm |
| Buitendiameter | 45 mm |
| Dikte | 17 mm |
| Gewicht | 99 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE