


Naaldhulslager NQIS25-22-JTEKT - NQIS25-22-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/nqis25-22-jtekt>

Machined ring needle roller bearings **Koyo**

F_w 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.		
F_w	d	D	B	C_r	C_{0r}	Oil lub.			Without inner ring		
32	25	47	22	31.2	41.4	14 000			—		
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.					
With inner ring				Without inner ring	With inner ring						
NQIS25/22				27	45	0.3	0.123	0.167	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952482842
Binnendiameter	25 mm
Buitendiameter	47 mm
Dikte	22 mm
Gewicht	167 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE