

Rollager NQ40-20-JTEKT - NQ40-20-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/roll/nq40-20-jtekt>

Machined ring needle roller bearings **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.		Without inner ring	
40	35	50	20	—	0.3	27.2	48.8	12 000	NQ40/20
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d ₂	D ₂	r ₂	0.085	0.129				
	min.	max.	max.						
	37	48	0.3						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952483030
Binnendiameter	40 mm
Binnendiameter	1.575" inch
Buitendiameter	50 mm
Buitendiameter	1.969" inch
Dikte	20 mm
Dikte	0.787" inch
Gewicht	85 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE