


Rollager NQI42-30-JTEKT - NQI42-30-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/roll/nqi42-30-jtekt>

Machined ring needle roller bearings **Koyo**
F_W 29 ~ 37 mm
With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|----|----|----|-------------------------|-----------------|------------------------------------|--|--------------------|-------------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | | Without inner ring | |
| 47 | 42 | 57 | 30 | 44.0 | 96.1 | 10 000 | | — | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| NQI42/30 | | | | 46 | 53 | 0.6 | — | 0.219 | — |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952483252 |
| Binnendiameter | 42 mm |
| Buitendiameter | 57 mm |
| Dikte | 30 mm |
| Gewicht | 219 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE