


# Rollager NA5908-JTEKT - NA5908-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/roll/na5908-jtekt>

Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	d	D	B	$B_1$	$C_r$	$C_{10}$	Oil lub.	Grease lub.	Without inner ring		
48	40	62	30	—	55.5	91.2	9 400	—	—		
					Mounting dimensions (mm)		(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
					With inner ring	Without inner ring	With inner ring	Without inner ring			
					$d_a$	$D_a$	$r_a$				
					min.	max.	max.				
					NA5908	44	58	0.6	0.187	0.313	IRM404830

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952483313
Binnendiameter	40 mm
Buitendiameter	62 mm
Dikte	30 mm
Gewicht	313 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE