


Naaldhulslager BK1512-JTEKT - BK1512-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bk1512-jtekt>

Boundary dimensions



Metric series with cage assembly

| Bearing No. | Boundary dimensions(mm) | | | | | Basic load ratings(kN) | | Fatigue load limit(kN) | Limiting speeds(min-1) | |
|-------------|-------------------------|----|----|---------|---------|------------------------|------|------------------------|------------------------|----------|
| | Fw | D | Cc | C3(min) | r3(max) | Cr | C0r | | Grease Lub. | Oil Lub. |
| BK1512 | 15 | 21 | 12 | 9.3 | 1 | 7,16 | 8,57 | 1,4 | 14000 | 21000 |

PRODUCTKENMERKEN

| | |
|----------------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3616060628961 |
| Binnendiameter | 15 mm |
| Buitendiameter | 21 mm |
| Dikte | 12 mm |
| Grenstoerental | 14000 rpm |
| Dynamische belasting | 7.16 kN |
| Statische belasting | 8.57 kN |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE