


Naaldhulslager HK2212-JTEKT - HK2212-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/hk2212-jtekt>

Boundary dimensions



Metric values with cage assembly

| Bearing No. | Boundary dimensions(mm) | | | | Basic load ratings(kN) | | Fatigue load limit(kN) | Limiting speeds(min-1) | | |
|-------------|-------------------------|----|----|---------|------------------------|------|------------------------|------------------------|----------|-------|
| | Fw | D | B | C-30mm) | C2 | C2* | | Grease lub. | Oil lub. | |
| HK2212 | 22 | 28 | 12 | — | 1 | 9.81 | 14.5 | 2.2 | 9600 | 15000 |

PRODUCTKENMERKEN

| | |
|----------------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3616060629258 |
| Binnendiameter | 22 mm |
| Buitendiameter | 28 mm |
| Dikte | 12 mm |
| Grenstoerental | 9600 rpm |
| Dynamische belasting | 9.81 kN |
| Statische belasting | 14.5 kN |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE