

Naaldhulslager JH-2212-JTEKT - JH-2212-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/jh-2212-jtekt>

Boundary dimensions



Inch series, with cage assembly

| Bearing No. | Boundary dimensions(mm) | | | | Basic load ratings(kN) | | Fatigue load limit(kN) | | Limiting speeds(min-1) | |
|-------------|-------------------------|-------|-------|--------|------------------------|-------|------------------------|-------------|------------------------|--|
| | Fw | D | C | Y(max) | Cr | Cor | Cu | Grease lub. | Oil lub. | |
| JH-2212 | 34,925 | 44,45 | 19,05 | 1,27 | 26,24 | 38,43 | 5,9 | 6100 | 9400 | |

PRODUCTKENMERKEN

| | |
|----------------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3616060630339 |
| Binnendiameter | 34.925 mm |
| Buitendiameter | 44.45 mm |
| Dikte | 19.05 mm |
| Grenstoerental | 6100 rpm |
| Dynamische belasting | 26.24 kN |
| Statische belasting | 38.43 kN |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE