


Naaldhulslager BAM1310-IKO - BAM1310-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam1310-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g																																																							
	Standard	Mass (Ref.) g	Closed end																																																																	
20.638 ($\frac{3}{16}$)	---	---	---	---	---	---	---	---	---	---	---	---	---																																																							
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="4">Standard mounting dimensions</th> <th colspan="2">Basic dynamic load rating</th> <th colspan="2">Basic static load rating</th> <th colspan="1">Allowable rotational speed⁽¹⁾</th> <th colspan="1">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th colspan="2">Shaft dia. ϕ</th> <th colspan="2">Housing bore dia. $J7$</th> <th>C</th> <th>C_0</th> <th>C_0</th> <th>N</th> <th>N</th> <th>rpm</th> <th>IRB 910</th> </tr> <tr> <td></td> <td></td> <td></td> <td>Max.</td> <td>Min.</td> <td>Max.</td> <td>Min.</td> <td>N</td> <td>N</td> <td>N</td> <td>N</td> <td></td> <td></td> <td></td> </tr> </thead> <tbody> <tr> <td>20.638</td> <td>26.988</td> <td>15.881</td> <td>20.638</td> <td>20.625</td> <td>27.000</td> <td>26.979</td> <td>9 870</td> <td>14 200</td> <td>19 000</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>														Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring	F_w	D	C	Shaft dia. ϕ		Housing bore dia. $J7$		C	C_0	C_0	N	N	rpm	IRB 910				Max.	Min.	Max.	Min.	N	N	N	N				20.638	26.988	15.881	20.638	20.625	27.000	26.979	9 870	14 200	19 000				
Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring																																																								
F_w	D	C	Shaft dia. ϕ		Housing bore dia. $J7$		C	C_0	C_0	N	N	rpm	IRB 910																																																							
			Max.	Min.	Max.	Min.	N	N	N	N																																																										
20.638	26.988	15.881	20.638	20.625	27.000	26.979	9 870	14 200	19 000																																																											

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173061
Binnendiameter	20.64 mm
Buitendiameter	26.99 mm
Dikte	15.88 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE