


Naaldhulslager BAM136-IKO - BAM136-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam136-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g																																																				
	Standard	Mass (Ref.) g	Closed end																																																														
20.638 ($\frac{13}{16}$)	—	—	—	—	—	—	—	—	—	—	—	—	—																																																				
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="4">Standard mounting dimensions</th> <th colspan="2">Basic dynamic load rating</th> <th colspan="2">Basic static load rating</th> <th colspan="1">Allowable rotational speed⁽¹⁾</th> <th colspan="1">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th colspan="2">Shaft dia. h6</th> <th colspan="2">Housing bore dia. J7</th> <th>C</th> <th>C_0</th> <th>C_0</th> <th>C_0</th> <th>rpm</th> <th></th> </tr> <tr> <td>20.638</td> <td>26.988</td> <td>9.521</td> <td>Max.</td> <td>Min.</td> <td>Max.</td> <td>Min.</td> <td>N</td> <td>N</td> <td>N</td> <td>N</td> <td></td> <td></td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>20.638</td> <td>20.625</td> <td>27.000</td> <td>26.979</td> <td>5 230</td> <td>6 300</td> <td>19 000</td> <td>—</td> <td>—</td> <td>—</td> </tr> </thead></table>														Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring	F_w	D	C	Shaft dia. h6		Housing bore dia. J7		C	C_0	C_0	C_0	rpm		20.638	26.988	9.521	Max.	Min.	Max.	Min.	N	N	N	N			—	—	—	20.638	20.625	27.000	26.979	5 230	6 300	19 000	—	—	—
Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring																																																					
F_w	D	C	Shaft dia. h6		Housing bore dia. J7		C	C_0	C_0	C_0	rpm																																																						
20.638	26.988	9.521	Max.	Min.	Max.	Min.	N	N	N	N																																																							
—	—	—	20.638	20.625	27.000	26.979	5 230	6 300	19 000	—	—	—																																																					

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173115
Binnendiameter	20.64 mm
Binnendiameter	13/16" inch
Buitendiameter	26.99 mm
Buitendiameter	1 1/16" inch
Dikte	9.52 mm
Dikte	0.375" inch
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE