



# Naaldhulslager BAM1412-IKO - BAM1412-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam1412-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Standard		Closed end		Standard		Closed end		Mass (Ref.) g		Grease retained	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g				
22.225 ( $\frac{7}{8}$ )	—	—	—	—	—	—	—	—	<b>BAM 1412</b>	26	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. $\phi$	Housing bore dia. $J7$	Max.	Min.	$C$	$C_0$	rpm	
22.225 $\frac{1}{2}$	28.575 $1 \frac{1}{4}$	19.05 (.750)	22.225	22.212	28.587	28.566	12 800	20 400	18 000	<b>IRB 1012</b>

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173139
Binnendiameter	22.23 mm
Buitendiameter	28.58 mm
Dikte	19.05 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE