


Naaldhulslager BAM1414-IKO - BAM1414-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam1414-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
22.225 (7/8)	—	—	—	—	—	—	—	BAM 1414	29.5	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F_w	D	C	Shaft dia. ϕ		Housing bore dia. ϕ		C	C_0	rpm		
			Max.	Min.	Max.	Min.	N	N			
22.225 (7/8)	28.575 (1 1/4)	22.22 (.875)	2.8	22.225	22.212	28.587	28.566	15 900	25 500	18 000	IRB 1014

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173146
Binnendiameter	22.23 mm
Buitendiameter	28.58 mm
Dikte	22.22 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE