

Naaldhulslager

BAM1418-IKO - BAM1418-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam1418-iko>

IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series



Shaft dia. mm (inch)	Identification number			Shaft dia. mm (inch)	Housing bore dia. mm (inch)	Basic dynamic load rating C _r N	Basic static load rating C ₀ N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end						
22.225 (7/8)	—	—	—	—	—	BAM 1418	37	—	—
Boundary dimensions mm(inch)									
F _w	D	C	B ₂	Shaft dia. mm h6	Housing bore dia. mm J7	C	C ₀		
22.225 ⁽¹⁾ ₀	28.575 ⁽¹⁾ ₀	28.58 ⁽¹⁾ ₀	2.8	22.225 ⁽¹⁾ ₀	22.212 ⁽¹⁾ ₀	28.587 ⁽¹⁾ ₀	28.566 ⁽¹⁾ ₀	19 800	35 600

Notes⁽¹⁾

Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.

Remark

Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173160
Binnendiameter	22.23 mm
Buitendiameter	28.58 mm
Dikte	28.58 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE