


Naaldhulslager BAM1516-IKO - BAM1516-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam1516-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end				
23.812 ($\frac{9}{16}$)	—	—	—	—	—	—	—
					BAM 1516	35.5	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm					
F_w	D	C	Shaft dia. mm Max. Min.	Housing bore dia. mm Max. Min.	N	N	
23.812 $\frac{9}{16}$	30.162 $1\frac{1}{8}$	25.40 1.000	23.812 23.799 30.176 30.151	30.176 30.151	18 900	34 300	16 000
<small>Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable. Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.</small>							

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173214
Binnendiameter	23.81 mm
Buitendiameter	30.16 mm
Dikte	25.4 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE