


Naaldhulslager BAM158-IKO - BAM158-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam158-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
23.812 ($\frac{9}{4}$)	—	—	—	—	—	—	—	BAM 158	19	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed(*)	Assembled inner ring		
F_w	D	C	f Max.	Shaft dia. h_8 Max. Min.	Housing bore dia. J7 Max. Min.	N	N	rpm	—		
23.812 $\frac{9}{4}$	30.162 $1\frac{1}{8}$	12.70 500	2.8	23.812 23.799	30.176 30.151	8 000	11 400	16 000	—		

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173221
Binnendiameter	23.81 mm
Buitendiameter	30.16 mm
Dikte	12.7 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE