

Naaldhulslager

BAM1614-IKO - BAM1614-IKO

https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam1614-iko

IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series



Shaft dia. mm (inch)	Identification number			Standard		Mass (Ref.) g		Closed end		Mass (Ref.) g		Grease retained (Ref.) g	
25.400 (1)	—	—	—	—	—	—	—	—	—	BAM 1614	33.5	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring
F _w	D	C	Shaft dia. h _s	Housing bore dia. J ₇	Max.	Min.	N	N	N	N	rpm		
25.400	31.750	22.22	25.400	25.387	31.764	31.739	16 900	30 400	15 000	IRB 1214			

Note⁽¹⁾

Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.

Remark

Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173252
Binnendiameter	25.4 mm
Buitendiameter	31.75 mm
Dikte	22.22 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE