


Naaldhulslager BAM166-IKO - BAM166-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam166-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Identification number			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end				
25.400 (1)	—	—	—	—	—	—	BAM 166	16	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ^(*)		Assembled inner ring
F_w	D	C	t	Shaft dia. mm Max. Min.	Housing bore dia. mm Max. Min.	C	C_0	N	N	
25.400	31.750	9.52	2.8	25.400 25.387	31.764 31.739	6 010	8 020	15 000	—	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173283
Binnendiameter	25.4 mm
Buitendiameter	31.75 mm
Dikte	9.52 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE