


## Naaldhulslager BAM168-IKO - BAM168-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam168-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number						Grease retained Mass (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g		
25.400 (1)	—	—	—	—	—	<b>BAM 168</b>	20.5	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed(*) rpm	Assembled inner ring
F <sub>w</sub>	D	C	Shaft dia. h <sub>s</sub>	Housing bore dia. J7	Max.	Min.				
25.400	31.750	12.700	25.400	25.387	31.764	31.739	8 240	12 000	15 000	<b>IRB 128</b>

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173306
Binnendiameter	25.4 mm
Buitendiameter	31.75 mm
Dikte	12.7 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE