


Naaldhulslager BAM1816-IKO - BAM1816-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam1816-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end				
28.575 (1 1/8)	---	---	---	BAM 1816	42.5	---	---

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
F _w	D	C	Shaft dia. h _s	Housing bore dia. J7	Max.	Min.				
28.575 (1 1/8)	34.925 (1 3/8)	25.40 (1.000)	28.575	28.562	34.930	34.914	20 500	40 900	13 000	IRB 1416

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173344
Binnendiameter	28.58 mm
Buitendiameter	34.93 mm
Dikte	25.4 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE