

Naaldhulslager

BAM208-IKO - BAM208-IKO

https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam208-iko

IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series



Shaft dia.		Identification number							
mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
31.750 (1 1/4)	—	—	—	—	BAM 208	26	—	—	—

Boundary dimensions mm (inch)			Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F _w	D	C ₁	Shaft dia. h ₈ /k ₇	Housing bore dia. J ₇ /h ₈	C	N	N	rpm	IRB 168
31.750 (1 1/4)	38.100 (1 1/2)	12.70 (1/2)	2.8	31.750 / 31.734	38.114 / 38.089	9 100	14 700	12 000	IRB 168

Note⁽¹⁾

Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.

Remark

Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173405
Binnendiameter	31.75 mm
Buitendiameter	38.1 mm
Dikte	12.7 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE