


## Naaldhulslager BAM45-IKO - BAM45-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam45-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
<b>6.350</b> (.25)	—	—	—	—	—	—	—	<b>BAM 45</b>	<b>2.7</b>	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. $h_8$	Housing bore dia. $J_7$		$C$	$C_0$	rpm		
6.350 (.25)	11.112 (.437)	7.921 (.312)	6.350 Max.	6.341 Min.	11.122 Max.	11.104 Min.	1 510	1 120	55 000	—

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173412
Binnendiameter	6.35 mm
Buitendiameter	11.11 mm
Dikte	7.92 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE