


Naaldhulslager BAM95-IKO - BAM95-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bam95-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
14.288 ($\frac{9}{16}$)	—	—	—	—	—	—	—	BAM 95	5.8	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring		
F_w	D	C	b_2	Shaft dia. h8	Housing bore dia. J7	C	C_0	rpm			
14.288 ($\frac{9}{16}$)	19.050 ($\frac{3}{4}$)	7.92 (.312)	1.3	14.288 Max.	14.277 Min.	19.062 Max.	19.041 Min.	2 780 N	2 970 N	30 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952173641
Binnendiameter	14.29 mm
Buitendiameter	19.05 mm
Dikte	7.92 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE