

## Kogellager enkele rij W6008-2RS1-SKF - W6008-2RS1-SKF

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/w6008-2rs1-skf>

Dimensions d'encastrement		Charges de base		Vitesses de base		Désignation
d	D	B	Dynamique C	statique C <sub>0</sub>	Vitesse de référence tr/min	Vitesse limite
40	68	15	14	10,8	-	6300

  

Technical drawing showing two views of the bearing. The left view shows the outer diameter (D = 68 mm), inner diameter (d = 40 mm), and thickness (B = 15 mm). The right view shows the bearing with seals, with dimensions for the outer diameter (D<sub>ext</sub> = 63,4 mm) and inner diameter (d<sub>int</sub> = 49,2 mm). A coefficient of seal is also indicated: k<sub>r</sub> 0,025 and t<sub>g</sub> 15.

### PRODUCTKENMERKEN

Merk	SKF
N° Ean13	7316570648621
Binnendiameter	40 mm
Waterdicht maken	Dubbelzijdige afdichting
Kooi	Plaatwerk
Radial class	CN
Buitendiameter	68 mm
Dikte	15 mm
Grenstoerental	6300 rpm
Gewicht	191 g
Dynamische belasting	14.6 kN
Statische belasting	11.4 kN
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE