

Kogellager enkele rij W6010-2RS1-SKF - W6010-2RS1-SKF

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/w6010-2rs1-skf>

Dimensions d'encadrement		Charges de base		Vitesses de base		Désignation
d	D	B	dynamique C	statique C ₀	Vitesse de référence tr/min	Vitesse limite
50	80	16	18,2	16	-	5000

Technical drawing showing front and side views of the bearing. Dimensions include: Bore diameter d = 50 mm, Outer diameter D = 80 mm, Width B = 16 mm, Groove diameter d₂ = 74,6 mm, Groove diameter d₁ = 60 mm, Groove width f_{1,2} = 1 mm, Groove depth r_{1,2} = 1 mm, Groove diameter D₂ = 75,4 mm, Groove depth r_{1,2} = 1 mm, Groove diameter d₂ = 60 mm, Groove depth r_{1,2} = 1 mm. Coefficients de calcul: k_r = 0,025, f₀ = 15.

PRODUCTKENMERKEN

Merk	SKF
N° Ean13	7316571664699
Binnendiameter	50 mm
Waterdicht maken	Dubbelzijdige afdichting
Kooi	Plaatwerk
Radial class	CN
Buitendiameter	80 mm
Dikte	16 mm
Grenstoerental	5000 rpm
Gewicht	270 g
Dynamische belasting	19 kN
Statische belasting	16.6 kN
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE