


Naaldhulslager CRY20-V-IKO - CRY20-V-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/cry20-v-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series **Full Complement Type /With Inner Ring**



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions: mm(inch)							
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C				
9.525 (3/8)	CRY 20 V		109	9.525 $\frac{3}{8}$	31.750 (1 1/4)	20.639(0.8125)	19.050 $\frac{3}{4}$				
a		F		Shaft dia.				Basic dynamic load rating C	Basic static load rating C ₀		
				Push fit		Drive fit				Press fit	
25.00(984)		1.588 (1/2)		Min.	Max.	Min.	Max.	Min.	Max.	N	N
				9.507	9.517	9.523	9.533	9.528	9.538	23 600	31 700

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952304175
Binnendiameter	9.53 mm
Buitendiameter	31.75 mm
Dikte	20.64 mm
Gewicht	103 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE